

## AMENDMENTS TO THE CLAIMS

1     **1. (Original)** A dual action canopy release buckle for releasably holding a parachute  
2     harness securement strap, said buckle having a frame with a forward end and a  
3     rearward end supporting a latch which may be pivoted between a locked-  
4     counterclockwise position and a released-clockwise position and being biased in a  
5     released-clockwise position and said latch being held in a locked-counterclockwise  
6     position by contact with a latch holding ledge supported by an actuating lever, said  
7     actuating lever having a distal end and a pivot end and said actuating lever being  
8     pivotable between a latch holding-clockwise position and a latch releasing-  
9     counterclockwise position and said actuating lever being biased toward a latch holding-  
10    clockwise position, wherein the improvement comprises:  
11         a lever arm pivotally held on the distal end of said actuating lever and extending  
12         upwardly therefrom and said lever arm having a distal, finger-contacting end and a pivot  
13         end, whereby when said distal, finger-contacting end of said lever arm is moved  
14         rearwardly the lever arm contacts a contacting end of said actuating lever and pulls the  
15         distal end of said actuating lever so that the actuating lever rotates in a  
16         counterclockwise direction to a latch releasing-counterclockwise position;  
17         a forward facing surface of said lever arm; and  
18         a contacting member secured to said frame and positioned so that a rearward  
19         edge of said contacting member contacts said forward facing surface of said lever arm  
20         at a point above said lever arm pivot pin whereby when said distal, finger contacting  
21         end of said lever arm is moved forwardly, said forward facing surface contacts said  
22         rearward edge and lifts the lever arm pivot pin thereby rotating said actuating lever in a  
23         counterclockwise direction to a latch releasing counterclockwise position whereby a  
24         dual action lever results in releasing the latch when the distal, finger contacting end of  
25         said lever arm is moved in a forward direction or a rearward direction.

2. **(Original)** The dual action canopy release buckle of claim 1 wherein said lever arm pivot pin is secured to a downwardly extending arm at the distal end of said actuating lever.
3. **(Original)** The dual action canopy release buckle of claim 1 wherein the rearward motion of the distal, finger-contacting end of said lever arm is limited by contact with the contacting end of said actuating lever.
4. **(Original)** The dual action canopy release buckle of claim 1 wherein said actuating lever includes a cross arm portion which extends inwardly from a latch holding ledge arm portion of said actuating lever.

1        5. **(Currently amended)** A dual action release buckle comprising:

2                a frame;

3                a latch moveably connected to the frame and adapted for releasably holding a  
4        tang in the buckle, the latch having a locked position wherein the tang is held, and an  
5        unlocked position wherein the tang is released;

6                an actuating member moveably connected to the frame and mechanically  
7        cooperating with the latch, wherein in a first position, the actuating member holds the  
8        latch in the locked position, and in a second position, the actuating member releases  
9        the latch thereby allowing the latch to move to the unlocked position;

10               a lever arm having a lever arm actuating end and a lever arm pivot end spaced  
11        apart from the actuating end, wherein the lever arm pivot end is pivotally coupled to the  
12        actuating member

13               a contacting end of the actuating member residing proximal to the lever arm;

14               a contacting member fixedly connected to the frame and residing proximal to a  
15        side of the lever arm opposite the actuating member, and between the actuating end of  
16        the lever arm and the lever arm pivot end ~~the distal end~~, and wherein:

17               motion of the lever arm actuating end in a first direction is directly coupled to the  
18        actuating member through contact of the lever arm with the contacting end of the  
19        actuating member, whereby the actuating member is movable from said first position to  
20        said second position; and

21               motion of the lever arm actuating end in a second direction is inversely coupled  
22        to the actuating member through the lever arm pivot end, wherein the lever arm  
23        contacts and pivots about the contacting member, whereby the actuating member is  
24        movable from said first position to said second position.

6. **(Original)** The buckle of Claim 5, wherein the contacting end is positioned to  
contact the lever arm between the lever arm actuating end and the lever arm pivot end.

7. **(Original)** The buckle of Claim 5, wherein the actuating member comprises an  
actuating lever pivotally coupled to the frame.

8. **(Original)** The buckle of Claim 7, wherein the actuating lever is pivotally coupled to the frame by an actuating lever pivot pin.

9. **(Previously amended)** The buckle of Claim 5, wherein the actuating member comprises an actuating slide slideably coupled to the frame.

10. **(Original)** The buckle of Claim 5, wherein the actuating member is biased into said first position.

11. **(Original)** The buckle of Claim 5, wherein said latch is biased into the unlocked position.

12. **(Original)** The buckle of Claim 5, wherein the actuating end of the lever arm includes a finger-contacting end adapted for manual manipulation.

13. **(Original)** The buckle of Claim 5, wherein the lever arm pivot end is pivotally coupled to the actuating lever by a lever arm pivot pin.

14. **(Original)** The buckle of Claim 5, wherein the latch is moveably connected to the frame and adapted for releasably holding a tang of a parachute harness securement strap in the buckle.

15. **(Original)** The buckle of Claim 5, wherein the actuating end of the lever arm required between approximately two pounds force to approximately fifteen pounds force to move the actuating member from the first position to the second position.

1       16. **(Previously amended)** A dual action canopy release buckle comprising:

2               a frame;

3               a latch moveably connected to the frame and adapted for releasably holding a  
4       tang of a parachute harness securement strap in the buckle, the latch having a locked  
5       position wherein the tang is held, and an unlocked position wherein the tang is  
6       released;

7               an actuating lever pivotally connected to the frame and mechanically cooperating  
8       with the latch, wherein in a first position, the actuating lever holds the latch in the locked  
9       position, and in a second position, the actuating lever releases the latch thereby  
10      allowing the latch to move to the unlocked position;

11              a lever arm moveably connected to the frame and having a lever arm  
12      actuating end and a lever arm pivot end, wherein the lever arm pivot end is pivotally  
13      coupled to the actuating lever;

14              a contacting end of the actuating lever residing adjacent to a portion of the lever  
15      arm between the lever arm pivot end and the lever arm actuating end; and

16              a contacting member fixedly connected to the frame and residing proximal to a  
17      side of the lever arm opposite the actuating lever, and between the actuating end and  
18      the pivot end, and wherein:

19              motion of the lever arm actuating end in a first direction is directly coupled to the  
20      actuating lever through contact of the lever arm with the contacting end of the actuating  
21      lever, whereby the actuating lever is movable from said first position to said second  
22      position of said actuating lever; and

23              motion of the lever arm actuating end in a second direction is inversely coupled  
24      to the actuating member through the lever arm pivot end, wherein the lever arm  
25      contacts and pivots about the contacting member, whereby the actuating member is  
26      movable from said first position to said second position.

17. **(Original)** The buckle of Claim 16, wherein the actuating end of the lever arm required between approximately two pounds force to approximately fifteen pounds force to move the actuating member from the first position to the second position.
18. **(Original)** The buckle of Claim 16, wherein the actuating lever is biased into said first position.
19. **(Original)** The buckle of Claim 16, wherein the actuating end of the lever arm includes a finger-contacting end adapted for manual manipulation.
20. **(Original)** The buckle of Claim 16, wherein said latch is biased into the unlocked position.